

RECEIVED
CENTRAL FAX CENTER
JUN 23 2008

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended) A solid electrolytic capacitor comprising:
 - a porous sintered body of valve metal; and
 - a metal case accommodating the porous sintered body;
 - wherein the metal case includes a main plate portion, and a side plate portion standing from a periphery of the main plate portion, the main plate portion and the side plate portion defining a hollow for accommodating the porous sintered body; and
 - wherein the metal case is provided with a plurality of anode terminals extending outward from the metal case so that a current can flow through the metal case via the anode terminals.
2. (Original) The solid electrolytic capacitor according to claim 1, further comprising a dielectric layer and a solid electrolyte layer which are formed at the porous sintered body, wherein the solid electrolyte layer acts as a cathode, the metal case is made of valve metal, and the metal case and the porous sintered body are electrically connected to each other to act as an anode.
3. (Canceled)
4. (Currently Amended) The solid electrolytic capacitor according to claim ~~[[3]]~~ 1, wherein the porous sintered body is flat and has a thickness which is smaller than a depth of the hollow of the metal case.
5. (Currently Amended) The solid electrolytic capacitor according to claim ~~[[3]]~~ 2, wherein the porous sintered body includes a first surface, and a second surface opposite to the first surface, the first surface being bonded to the main plate portion of the metal case directly or indirectly.

6. (Original) The solid electrolytic capacitor according to claim 5, wherein the first surface of the porous sintered body is bonded to the main plate portion of the metal case via a bonding material containing valve metal powder.

7-8. (Canceled)

9. (Currently Amended) The solid electrolytic capacitor according to claim [[7]] 1, wherein the anode terminals [[is]] are integrally formed on the side plate portion of the metal case.

10. (Currently Amended) The solid electrolytic capacitor according to claim [[7]] 1, further comprising a metal member made of a same material as the metal case and bonded to the metal case, wherein part of the metal member serves as the anode terminals.

11. (Original) The solid electrolytic capacitor according to claim 5, wherein part of the solid electrolyte layer is provided on the second surface of the porous sintered body, and wherein the solid electrolytic capacitor further comprises a metallic connecting member made of metal and bonded to said part of the solid electrolyte layer, part of the metallic connecting member serving as a cathode terminal.

12. (Currently Amended) ~~The solid electrolytic capacitor according to claim 11,~~ A solid electrolytic capacitor comprising:

a porous sintered body of valve metal;

a metal case accommodating the porous sintered body;

a dielectric layer formed on the porous sintered body; and

a solid electrolyte layer formed on the dielectric layer to act as a cathode;

wherein the metal case and the porous sintered body are electrically connected to each other to act as an anode;

wherein the metal case includes a main plate portion, and a side plate portion standing from a periphery of the main plate portion, the main plate portion and the side plate portion defining a hollow for accommodating the porous sintered body;

wherein the porous sintered body includes a first surface, and a second surface opposite to the first surface, the first surface being bonded to the main plate portion of the metal case directly or indirectly;

wherein part of the solid electrolyte layer is provided on the second surface of the porous sintered body;

wherein the solid electrolytic capacitor further comprises a metallic connecting member made of metal and bonded to said part of the solid electrolyte layer, part of the metallic connecting member serving as a cathode terminal

wherein the metal case is formed with a cutout, and

wherein part of the metallic connecting member extends from inside to outside of the metal case by passing through the cutout.

13. (Currently Amended) The solid electrolytic capacitor according to claim ~~[[11]]~~ 12, wherein the second surface of the porous sintered body includes a periphery formed with an insulating layer, and wherein said part of the solid electrolyte layer on the second surface is formed at a region surrounded by the insulating layer.

14. (Original) The solid electrolytic capacitor according to claim 13, wherein the insulating layer is made of resin, and wherein part of the resin is impregnated into a peripheral portion of the porous sintered body.

15. (Currently Amended) The solid electrolytic capacitor according to claim ~~[[1]]~~ 12, wherein the metal case includes an irregular inner surface, ~~and the inner surface is bonded to the porous sintered body.~~

16. (Currently Amended) ~~The solid electrolytic capacitor according to claim 1, A solid electrolytic capacitor comprising:~~

a porous sintered body of valve metal; and

a metal case accommodating the porous sintered body;

wherein the metal case includes an inner surface to which a metal member made of valve metal is welded to form a projection.

17. (Currently Amended) ~~The solid electrolytic capacitor according to claim 1,~~ A solid electrolytic capacitor comprising:

a porous sintered body of valve metal; and

a metal case accommodating the porous sintered body;

wherein the metal case includes an inner surface formed with a plurality of recesses and a plurality of burrs corresponding to the recesses.

18. (Currently Amended) ~~The solid electrolytic capacitor according to claim 1,~~ A solid electrolytic capacitor comprising:

a porous sintered body of valve metal; and

a metal case accommodating the porous sintered body;

wherein the metal case includes an inner surface at which a plurality of projections are formed by partially bulging the metal case.

19. (Currently Amended) The solid electrolytic capacitor according to claim ~~[[1]]~~ 18, wherein the metal case includes an opening which is closed with resin.

20. (Currently Amended) ~~The solid electrolytic capacitor according to claim 1,~~ A solid electrolytic capacitor comprising:

a porous sintered body of valve metal; and

a metal case accommodating the porous sintered body;

wherein the metal case includes an outer surface which is at least partially covered with resin.

21-22. (Canceled)

23. (Currently Amended) A method for manufacturing a solid electrolytic capacitor including a metal case and a porous sintered body accommodated in the metal case, the method comprising:

~~a first step of preparing the metal case; and~~

~~a second step of preparing the porous sintered body; and~~

forming a dielectric layer and a solid electrolyte layer at the porous sintered body;
wherein the porous sintered body includes a bonding surface bonded to the metal case
and a non-bonding surface which is not bonded to the metal case;

wherein the step of forming the dielectric layer and the solid electrolyte layer comprises
forming the dielectric layer and the solid electrolyte layer at an interior and the non-bonding
surface of the porous sintered body; and

wherein an insulating layer is formed at a periphery of the non-bonding surface of the
porous sintered body before formation of the solid electrolyte layer so that the insulating layer
prevents the solid electrolyte layer from being formed at the periphery of the non-bonding
surface.

24. (Currently Amended) The manufacturing method according to claim 23, wherein the ~~second~~
step preparation of the porous sintered body includes compacting valve metal powder put in the
metal case to provide a porous body, and heating the porous body together with the metal case to
provide a porous sintered body.

25. (Currently Amended) The manufacturing method according to claim 23, wherein the ~~second~~
step preparation of the porous sintered body includes bonding a porous body of valve metal
powder into the metal case by using a bonding material containing valve metal powder, and
heating the porous body with the metal case to provide a porous sintered body.

26. (Currently Amended) The manufacturing method according to claim 23, wherein the ~~second~~
step preparation of the porous sintered body includes bonding a porous sintered body of valve
metal powder into the metal case by using a bonding material containing valve metal powder.

27. (Currently Amended) The manufacturing method according to claim 23, wherein the ~~first~~
step preparation of the metal case includes subjecting a metal frame to drawing.

28. (Canceled)

29. (Currently Amended) The manufacturing method according to claim ~~[[28]]~~ 23, wherein the metal case includes an opening defined by a plurality of side plate portions, and wherein the ~~step of forming~~ formation of the dielectric layer and the solid electrolyte layer is performed by setting the metal case to be open upward and pouring treatment liquid for forming the dielectric layer or the solid electrolyte layer into the metal case through the opening.

30. (Canceled)

31. (Currently Amended) ~~The manufacturing method according to claim 28, further comprising the step of~~ A method for manufacturing a solid electrolytic capacitor including a metal case and a porous sintered body accommodated in the metal case, the method comprising:

preparing the metal case;

preparing the porous sintered body; and

forming a dielectric layer and a solid electrolyte layer at the porous sintered body;

wherein the porous sintered body includes a bonding surface bonded to the metal case

and a non-bonding surface which is not bonded to the metal case;

wherein the step of forming the dielectric layer and the solid electrolyte layer comprises forming the dielectric layer and the solid electrolyte layer at an interior and the non-bonding surface of the porous sintered body;

wherein providing, after the formation of the dielectric layer and the solid electrolyte layer, a metal member at the non-bonding surface of the porous sintered body after the formation of the dielectric layer and the solid electrolyte layer so that the metal member is electrically connected to the solid electrolyte layer[.]; and

wherein part of the metal member is extended out of the metal case to act as a cathode terminal.

32. (Original) The manufacturing method according to claim 31, further comprising the step of loading resin into the metal case to seal part of the metal member with the resin after the metal member is provided at the non-bonding surface.

33. (Original) The manufacturing method according to claim 31, further comprising the step of covering an outer surface of the metal case with resin.